



AOPEN

Bright Ideas Connected

Digital Engine®



Cost effective UHD (4k) Media Player with AiCU **DE3450**

A value range device based on the reliable Intel® Quad Core Apollo Lake® Processor J3455, which is capable of running UHD playback. The DE3450 supports Ultra HD (4K) resolution and HEVC/H.265 10 bit high-definition video playback. The solid-state disk and fanless design of this player ensure a first rate of performance in any challenging situation.

Features include:

- + Including the AOPEN intelligent Control Unit (**AiCU**)
- + Supports Ultra HD (4K@60p) resolution and HEVC/H.265 & VP9 high-definition video playback
- + Dual Giga LAN and Dual Wifi antenna makes it a perfect solution for IOT gateway applications.
- + Two HDMI ports (1x 2.0, 1x 1.4)
- + Support TPM2.0, the use of validated encryption key brings extra security to your device
- + Watchdog timer for device monitoring and control

SUPER
RTC



EDID
Emulator



SYSTEM DATA
Record





HDMI
Cable detection



REMOTE
Control



DE3450



Model Name		DE3450	
Form Factor		Fanless & Non-venting hole design	
Dimension	W x H x D (mm)	166 x 25 x 158 mm	
	W x H x D (inch)	6.54 x 0.98 x 6.22 inch	
Volume		0.65 L	
Single Pack Weight	N.W.	0.8 kg/ 1.76 lb	
	G.W.	1.5 kg/ 3.31 lb	
CPU	Socket	CPU on board	
	Type	Support Intel Apollo lake D Quad Core J3455 (TDP>=10W),	
Chipset		CPU Build-in	
Memory		Dual Channel, DDR3L SO-DIMM x 2, 1866 MHz, up to 8GB	
Graphics	Chip	Intel HD Graphics 500	
Expansion Slot		M.2 2242 x 1 (key B for SSD) M.2 2230 x 1 (key E for WIFI)	
Audio	Type	Realtek HD Audio ALC269Q	
	Channel	Stereo	
LAN		Realtek Gigabit Ethernet RTL8111H x 2 10/100/1000Mbps	
Storage Bay		M.2 SSD	
Front Panel IO	USB 2.0 Port	-	
	USB3.0 Port	x 2	
	Others	RS232 DB9 x 1/ Antenna Hole x 2	
		DC Jack	x 1
		HDMI Port	x 2 (HDMI2.0 x 1 / HDMI1.4b x 1)
		DisplayPort	-
		USB 2.0 Port	-
		USB 3.0 Port	x 2
		eSATA Port	-
		RJ45 LAN Port	x 2
		Legacy RS232 Serial Port (COM Port)	-
		Audio set	Line-Out x 1
			Mic-In x 1
		Upgrade for Antenna Port	-
		Kensington Security Slot	-
		Others	Extend Power SW x 1
		On Board I/O	Internal USB2.0 pin head x 2, SATA (FCC type) connector x 1
		Adapter	40W (19V, 2.1A) AC Adapter
		WatchDog Timer	1 ~ 255 SEC./ min
		Input Voltage	AC 100 ~ 240V
Environment			
		MTBF	50,000hrs
		Operating Temperature	0 ~45°C (32 ~ 113°F)
		Storage Temperature	-20 ~ 60°C (-4 ~ 140°F)
		Relative Humidity	95% RH (45°C non-Condensing)

*Accessories available on demand

The specifications depicted may be subject to change without prior notice. All trademarks are copyright of their respective owners. © AOPEN Inc. All Rights reserved.

