









Fanless, Slim & Robust 8K Media Player

DEX5750-S

The DEX5750-S, a fanless design computer supporting 11th Gen Intel® Core $^{\text{TM}}$ processors, provides a blend of performance and efficiency. This low-power platform, based on our 10nm process technology, features Intel® Iris® Xe graphics for up to 2.95 times faster graphics performance. Ideal for digital applications, the DEX5750-S operates seamlessly even in challenging, greasy, or dusty environments.

The DEX5750-S features:

- + 11th Generation Intel® Core (available in i3, i5)
- + DDR4 dual channel memory, up to 64GB (based on OS support)
- + Support WiFi 6 module
- + Supports HEVC/H.265 video playback
- + Support -20°C (-4°F) operating temperature
- + Support AOPEN AiCU-OOB technology (optional)

DEX5750-S





| Model name DEX5750-S | | | | |
|----------------------|---------------------|--|--|--|
| Dimension | W x H x D (mm) | 240 x 25 x 158 mm | | |
| | W x H x D (inch) | 9.44 x 0.98 x 6.22 inch | | |
| Volume | | 0.95L | | |
| Weight | | 1.87 kgs / 4.12 lbs | | |
| СРИ | Socket | CPU on board | | |
| | Туре | Intel® 11th Gen Tiger Lake UP3 TDP=15W | | |
| Chipset | Туре | - | | |
| Memory | Channel | Dual Channel | | |
| | Туре | DDR4 SO-DIMM x 2 | | |
| | Data rate | 3200 | | |
| | Max Memory | 64GB | | |
| Graphics | Chip | Intel® Iris Xe Graphics | | |
| Expansion | Mini card | - | | |
| | Mini card half size | - | | |
| | M.2 2230 | x 1 | | |
| | M.2 2242 | x 1 | | |
| | M.2 2280 | x 1 | | |
| Audio | Туре | Realtek HD Audio ALC269Q | | |
| | Channel | Stereo | | |
| | | Intel® GIGA LAN x 1 (i219LM) | | |
| LAN | | 100/1000/2500 Mbps | | |
| Storage Bay | 2.5" SATA HDD | - | | |
| | M.2 SSD | x 2 | | |

| | USB 2.0 Port | | x 2 | | |
|-----------------------|----------------------|----------|--------------------------------|--|--|
| Front Panel I/O | USB 3.1 Port | | - | | |
| | Others | | RS232 x1, RS232/422/485 x1 | | |
| Rear Panel I/O | DC Jack | | 12~24V | | |
| | HDMI 2.0 Port | | x 2 | | |
| | USB 2.0 Port | | - | | |
| | USB 3.1 Port gen 2 | | x 4 | | |
| | eSATA Port | | - | | |
| | RJ45 LAN Jack | | x 2 | | |
| | Display Port | | - | | |
| | Audio Set | Line-Out | x 1 | | |
| | | Mic-in | x 1 | | |
| | Antenna Holes | | x 2 | | |
| | Kensington Lock Hole | | - | | |
| | COM Port | | - | | |
| | Others | | Extend Power Switch | | |
| CPU Thermal Module | | | AOpen Thermal Module | | |
| WatchDog Timer | | | 1 ~ 255 SEC./ min | | |
| Adapter | | | 90W (19V, 4.74A) Power Adapter | | |
| Input Voltage | | | AC 100 ~ 240V | | |
| Environment | | | | | |
| MTBF | | | 50,000hrs | | |
| Operating Temperature | | | -20 ~45ºC (-4 ~ 113ºF) | | |
| Storage Temperature | | | -30 ~ 60°C (-22 ~ 140°F) | | |
| Relative Humidity | | | 90% RH (60ºC non-Condensing) | | |
| | | | | | |

Supports:







The specifications depicted may be subject to change without prior notice. All trademarks are copyright of their respective owners. \otimes AOPEN Inc.



Tokyo, Japan

AOPEN Japan AOPEN China Shanghai, China