



Rugged & Compact

Fanless | Slim Type | 4K@60Hz


DE3129-S

The DE3129-S is a slim-type, fanless industrial PC (IPC) powered by the Intel® N100 Processor. It supports 4K UHD playback, operates reliably in -20°C to 45°C environments, and features Intel® PTT TPM 2.0 for enhanced security. Its fanless, solid-state design ensures silent operation, reduced maintenance, and improved durability. With its compact form factor and wide 12–24V DC input, the DE3129-S is ideal for space-constrained deployments in the retail and social recreation markets, including kiosks, digital signage, and interactive displays.

- Supports Intel® N 100 Processor, TDP=6W
- Supports UHD(4K, 3840x2160@60Hz) content playback
- Supports -20°C ~45°C operating temperature
- Fanless and solid-state design
- Supports Intel® PTT TPM2.0
- DC input 12 ~ 24V for automotive applications



DE3129-S



Model name		DE3129-S
Feature		Fanless and Slim
Color		Black
Dimensions	W x H x D (mm)	166 x 25 x 158 mm
	W x H x D (inch)	6.54 x 0.98 x 6.22 inch
Volume		0.65 L
Weight		0.8 kgs / 1.76 lbs
CPU	Type	Intel® N 100 Processor, TDP=6W
Memory	Channels	Single Channel
	Type	DDR5 SO-DIMM
	Data Rate	4800 MHz
	Max Memory	Max 16GB
Graphics		Intel® UHD Graphic Gen12
Expansion slot		M.2 2230 x 1 (key E for Wifi) M.2 2280x1 (key M for SATA SSD/PCIe SSD)
Audio	Type	Realtek HD Audio Codec ALC897
	Channel	Stereo
LAN	Chip	Intel 2.5G LAN x1 (i226V)
	Speed	100 / 1000 / 2500 Mbps
Storage	2.5" Bay	-
	M.2 SSD	X 1

Front Panel I/O	USB Port	X 2 (2.0 Port)
	Power Button	X 1
	Others	-
Rear Panel I/O	DC Input	X 1 (12~24V)
	HDMI Port	X 1 (HDMI 2.0)
	Display Port	-
	USB Port	X4 (USB2.0 x2, USB3.2 x2)
	eSATA Port	-
	RJ45 LAN Jack	X 1
	COM Port	-
	Antenna Holes	X 2
	Kensington Lock Hole	-
	Others	Combo Audio Jack x1, Extend Power SW x1
Watchdog Timer		1 ~ 255 sec/min
Adapter		45W (19V, 2.37A) AC Adapter
Input Voltage		AC 100 ~ 240V
Warranty		2 Years
Environment		
MTBF		50,000 hrs
Operating Temperature		-20°C ~ 45°C (-4°F ~ 113°F)
Storage Temperature		-30°C ~ 60°C (-22°F ~ 140°F)
Relative Humidity		90% RH (35°C Non-Condensing)

Supports



*Please note that product specifications are subject to change without notice



AOPEN Headquarter
New Taipei City,
Taiwan

AOPEN America
San Jose,
USA

AOPEN Europe
S'Hertogenbosch,
Netherlands

AOPEN Australia
Melbourne,
Australia

AOPEN Japan
Tokyo,
Japan

AOPEN China
Shanghai,
China

v3.0